



HORRON
www.horron.com



H900 Electrolyte Analyzer

- 7" Color touch screen, easy to operate
- High accurate and long life electrode and TCO₂ sensor
- Programmable multi-format print-out
- Reagent pack, real time monitoring of reagent residual volume
- Up to 50,000 test results can be stored
- RS-232 port, supporting bar code reader and USB interface
- Sleep mode to reduce reagent consumption
- Option: Sample tray

H900 Electrolyte Analyzer

Parameter configuration:

A K, Na, Cl
B K, Na, Cl, TCO₂
C K, Na, Cl, iCa, nCa, TCa, pH
D K, Na, Cl, iCa, nCa, TCa, pH, TCO₂, Ag
F K, Na, Cl, Li
G K, Na, Cl, Li, TCO₂
H K, Na, Cl, iCa, nCa, TCa, pH, Li
I K, Na, Cl, iCa, nCa, TCa, pH, Li, TCO₂, Ag
J K, Na, Cl, iCa, nCa, TCa, pH, Mg, TCO₂, Ag
K K, Na, Cl, iCa, nCa, TCa, pH, Li, Mg, TCO₂, Ag

Measuring speed: ≤ 25s
Sample volume: 60–300ul (item 3 to item 11)
Sample position: 39 positions (including 5 emergency and 2 QC)

Storage: up to 10000 test results
Printer: Internal thermal printer
Interface: RS232 port

Working environment:

Temperature: 10–30°C
Relative Humidity: ≤ 80 %
Atmospheric pressure: (86~106) kPa
Power supply: AC220V ± 22V, 50Hz ± 1Hz
Power: ≤ 120W

Specification:

Sample: serum, plasma, whole blood, cerebrospinal fluid and dilute urine
Analysis Method: ion selective electrode (ISE)

Dimension: 340mm*200mm*380mm
Net weight: 6Kg

Items	Measuring Range	Resolution	Measuring Precision(CV%)
K ⁺	0.5–20.0mmol/L	0.01 mmol/L	≤ 1.0%
Na ⁺	15–200mmol/L	0.1 mmol/L	≤ 1.0%
Cl	15–200mmol/L	0.1 mmol/L	≤ 1.0%
Ca ²⁺	0.1–6.0mmol/L	0.01 mmol/L	≤ 1.0%
Li ⁺	0.1–5.0mmol/L	0.01 mmol/L	≤ 2.0%
pH	4–9pH	0.01 pH	≤ 0.5%
TCO ₂	2.0–70.0mmol/L	0.1 mmol/L	≤ 3.0%

Main Features:

- Human-machine interactive menu; Dynamic and real-time display of sample ID.
- Liquid level automatic detection and alarming. Real-time diagnostic of system working status.
- Automatically detect and filter tiny bubbles to avoid clog and ensure accurate measurement.
- Wave theory flushing method and direct flushing pipe method to avoid block and crossed contamination.
- Automatic calibration and two-point correction to adjust slope and intercept; Available to print-out QC graph and QC statistical parameters.
- Power failure protection to avoid data losing. Data storage could be extended to more than 50000. Supporting fuzzy query.
- Supporting LIS software; Upload data format is selectable; Supporting RTC Clock management.
- Available to power off any time, therefore reduce reagent consumption, suitable for any hospitals.

HORRON XHL Electronics

Australia Office :

23 Crimson Grove, Clayton South, VIC 3169, Australia
Tel : +61 03 95478575
Fax : +61 03 95578575
Email : export@horron.com, horron.xlh@gmail.com
Website : www.horron.com

China Office :

7th floor, 4th Building, Fantasia MIC Plaza,
NanHai Road, Shenzhen 518067, China
Tel : +86 755 26855736
Fax : +86 755 26855736 127